DecoRad®
ACCELERATED DRYING AND CURING

DecoRad® Systems bv
Kernreactorstraat 11B
3903 LG Veenendaal

T: +31(0)318-550425
F: +31(0)318-554340
E: info@decorad.com

SPECIFICATIONS DECORAD® FLOORMATE

General	Automatic
Description	DecoRad® Floormate
Brand	DecoRad®
Colour	Silver / black
Cure path	45cm
Lamphouse height adjustable (mm)	✔
Zero degree turn radius	✔
Adjustable cure speed	Yes
Wheels with PU tyre	✔
Introduction	July 2011
Measurements and weights	
Total weight (kg)	Apx. 50
Measurements (cm)	70 x 50 x 50 (L x W x H)
Power supply	
Power UV - ultraviolet (Watt)	3000
Power supply	230 Vac 50 HZ
Imax	16 A
Cable powering (cm)	1000
Lamps	
Type UV-lamp(s)	UVE-500v3000W
Number of UV lamp(s)	1
Burning hours UV-lamp(s)	>1000
Start-up time UV-lamp(s)	> 45 secondes
Ozone	Free
Warranty (excluding UV lamp)	
Manufacturer's warranty	1 year
Warranty type	Carry-in
Inspections	
CE Approved	✔
TÜV certified (radiation)	✔
Accessories	
Standard:	Service and repair manual, facial shield, heat shield, extention card
Optional:	Flightcase, Lamp + housing + reflectors, Extra PCB (mainprint), Safety cones, Extra set of wheels (as a package or individually available)

Sustainable job progress with DecoRad®

Model changes and misprints reserved. Nothing from this publication can be multiplied, stored in an automated file and/or made public in any form, either electronically, mechanically by meansof printing, photocopy, or any other way without prior written consent of DecoRad® Systems bv.